

## W-Series

High Performance, high attenuation, 2-stage

12704 W. Arden Place  
Butler, WI 53007 USA


Phone: 262-790-0092

Fax: 262-790-0095

Website: www.emissioncontrol.com

E-mail: info@emissioncontrol.com

### Part Number System



### Agency Approvals:



Part Number	Current Rating Amps	Schematic
W6Q	6	
W10Q	10	
W16Q	16	

### Electrical Specs

Rated Voltage: 250VAC 50/60 Hz.

Rated Current: @ 40° C

Hipot Rating:

Line to Ground: 1800 VAC, 2 sec.

Line to Line: 1700 VDC, 2 sec.

Climatic Category: HPF (25/085/21)

Maximum leakage current:

each line to ground  
@ 250 VAC 50 Hz 3.4ma

Minimum insertion loss — dB (50 ohm circuit)

Current Rating	Mode	Frequency - MHz							
		.01	.05	.15	.5	1	5	10	30
6	Common	15	30	43	55	61	65	64	51
	Differential	27	41	56	39	53	63	61	58
10	Common	11	25	39	52	58	65	63	53
	Differential	27	41	55	35	50	52	59	56
16	Common	6	19	34	50	55	65	65	56
	Differential	27	41	55	43	40	53	50	46

\* Low leakage medical versions  
Available to meet UL544

### Mechanical Specs

Construction: Metal case and cover. Internal components and terminations sealed with self-extinguishing resin.

Connections: Q = Quick Connects  
.25" (6.3) x .03" (0.8)

Dimensions: inches  
(mm)

